

IN THE CLAIMS:

Please amend Claims 1, 2, 8, 13 and 20 as follows:

1. (Twice Amended) A gas laser device, comprising:
a chamber for sealingly storing a laser gas therein[,
and for producing light amplification through reflection of light
between a total reflection window and an exit window];

a discharging electrode for exciting the laser gas
through electrical [discharge, so that laser light is outputted
from said chamber] discharging;

a total reflection mirror for amplifying laser light
produced by the electrical discharging from said discharging
electrode;

an output window for amplifying the laser light and
for outputting a portion of the laser light amplified between
said total reflection mirror and said output window;

a blower for circulating the laser gas within said
chamber, so that the laser gas passing an electrical discharging
region of said discharging electrode is circulated in said
chamber and is returned to the electrical discharging region of
said discharging electrode; and

control means for [changing] controlling revolutions
of said blower [between (i) an in-operation state in which the

laser gas is excited by] in accordance with a state of the
electrical [discharge] discharging from said discharging
electrode [and] so that the [laser light is being outputted, and
(ii)] revolutions of said blower a stand-by state [in which no
laser light is emitted, but an output of the laser light is being
prepared] are made less than the revolutions in an in-operation
state, wherein the stand-by state is a state in which no laser
gas is excited by the electrical discharging from said
discharging electrode and thus no laser light is emitted whereas
an output of the laser light is being prepared, and wherein the
in-operation state is a state in which the laser gas is excited
by the electrical discharging from said discharge electrode and
the laser light is being outputted.

B2
Coul
C2
Coul.

2. (Twice Amended) A gas laser device according to
Claim 1, wherein said control means [stops] controls the
revolutions of said blower when said gas laser device is in the
stand-by state by stopping the blower.

8. (Twice Amended) A gas laser device according to
Claim 7, wherein said control means [stops] controls the
revolutions of said blower when said gas laser device is in the
stand-by state by stopping the blower.

B3
Coul
C3

13. (Twice Amended) An exposure apparatus,
comprising:

By
C4

a laser light source having (i) a chamber for sealingly storing a laser gas therein [and for producing light amplification through reflection of light between a total reflection mirror and an exit window], (ii) a discharging electrode for exciting the laser gas through electrical [discharge so that laser light is outputted from said chamber] discharging, [and] (iii) a total reflection mirror for amplifying laser light produced by the electrical discharging from said discharging electrode, (iv) an output window for amplifying the laser light and for outputting a portion of the laser light amplified between said total reflection mirror and said output window, and (v) a blower for circulating the laser gas within said chamber so that the laser gas passing an electrical discharging region of said discharging electrode is circulated in said chamber and is returned to the electrical discharging region of said discharging electrode;

a main assembly for exposing a substrate to the laser light from said laser light source; and

control means for [changing] controlling revolutions of said blower [between (i) an exposure-operation state of said exposure apparatus in which exposure of the substrate to the laser light from said laser light source can be performed through

amplifying laser light produced by the electrical discharging from said discharging electrode by a total reflection mirror;

amplifying the laser light by an output window and outputting a portion of the laser light amplified between said total reflection mirror and said output window;

circulating, using a blower, the laser gas within the chamber, so that the laser gas passing an electrical discharging region of the discharging electrode is circulated in the chamber and is returned to the electrical discharging region of the discharging electrode; and

CG 10/25/01
[changing, using control means,] controlling revolutions of the blower [between (i) an in-operation state in which the laser gas is excited by the electrical discharge from the discharging electrode and the laser light is being outputted, and (ii) a stand-by state in which no laser light is emitted, but an output of the laser light is being prepared] in accordance with a state of electrical discharging from said discharging electrode, so that the revolutions of the blower in a stand-by state are made less than the revolutions in an in-operation state, wherein the stand-by state is a state in which no laser gas is excited by the electrical discharging from said discharging electrode and thus no laser light is emitted whereas an output of the laser light is being prepared, and wherein the